

PT. BUDIJAYA CEMERLANG ABADISEJAHTERA

sales@bcasejahtera.com | www.bcasejahtera.com | Hotline: +62811-6047-010

SALES - SERVICE - PARTS

YOUR PARTNER FOR GREEN & PROFIT SOLUTION

SAND CYCLONE SINGLE / DOUBLE STAGE

MODEL

SCSS/SCDS 40/50 - 30TPH

SCSS/SCDS 40/50 - 45TPH

ENHANCED WITH 2 VARIOUS CONTROL SYSTEM

NEW VERSION 2022







THE ADVANTAGES of OUR PRODUCT & OVERVIEW

- Our SPECIALLY designed Single Stage Sand Cyclone has functions to take the fine sand contained in the sludge, prevent sludge separator or decanter FREE from fast wear-and-tear
- 2. BEST installed before Sludge Centrifudge/ Decanter
- **3.** PROVEN Quality for sand removal system with centrifuge force to ensure discharging maximal sand
- 4. 2 VARIOUS Control System to choose to suit your budget
- 5. ONLY USE Cast Nylon Cone for Longer Life-Time

SPECIFICATION

- 1 Unit Stainless Steel 316 Top Cylinder
- 1 Unit Teflon Cone (Cast Nylon)
- 2 Unit Piston Valve for Flushing (1/2", 1")
- 1 Pcs 1-1/2" Top SS316 HP VTV Ball Valve
- 1 Pcs 2" Bottom SS316 HP VTV Ball Valve
- 1 Unit Stainless Steel Dirt receiver with sight glass
- 2 Pcs Pneumatic Actuators DA c/w 2 pcs Solenoid 220VAC
- 1 Unit Pad Control Panel For autodischarge system
- 1 Pcs Pressure Gauge 4" 0-6 Bar in inlet
- 1 unit Base Plate Mounted (200w/220v/50Hz)



AVAILABLE FOR WEAR-AND-TEAR SPARE PARTS



- 1 Teflon Cone (Cast Nylon)
- 2 Piston Valve for Flushing (1/2", 1")
- **3** VTV HP Ball Valve model BV 301/302 (1,5"& 2")
- 4 Repair Kit RTFE Seat for 1-1/2" SS316 HP VTV Ball Valve
- **6** Repair Kit RTFE Seat for 2" SS316 HP VTV Ball Valve
- 6 VTV Pneumatic Actuators DA
- **7** VTV Solenoid Valve 220VAC
- 8 Pressure Gauge WIKA 233.50.100 (0-6 barG) C/W diaphragm seal

RECOMMENDED RUNNING PROCEDURE

- The timer control is set 5 minutes (Closed),
 while it is 10 15 seconds (Open)
- DP inflow to outflow is 2barG



BCAS

PT. BUDIJAYA CEMERLANG ABADISEJAHTERA

WAREHOUSE

JI. Sangir Talaud I KIM IV, Desa Pematang Johar, Kec. Labuhan Deli Kab. Deli Serdang, Medan, Sumatera Utara Telp.: (061) 786 2299 | Fax.: (061) 787 4188