

PT. BUDIJAYA CEMERLANG ABADISEJAHTERA

sales@bcasejahtera.com | www.bcasejahtera.com | Hotline: +62811-6047-010

SALES - SERVICE - PARTS



Gain More Profit

Specially Designed to Reduce Efficiently Moisture/Oxygen in Crude Palm Oil to Gain More Profit

Fully-Coated External

Fully-Coated External with Wore Brush with 2-times of Oxide Primper Paint

Low Maintenance

Guaranteed for Low Maintenance and Low Operational Cost

Maximize Spraying

Nozzle are Perfectly-placed to Maximize Spraying to Take-out Unwanted Moisture

WAREHOUSE

Jl. Sangir Talaud I KIM IV, Desa Pematang Johar, Kec. Labuhan Deli Kab. Deli Serdang, Medan, Sumatera Utara Telp.: (061) 4273 1118 | Fax.: (061) 4273 1119



SPECIFICATION

Vacuum Oil Dryer-Capacity : 12 - 15 TPH
Operation Temperature : ± 90 deg C

Operation Vacuum : (-) 700 to (-) 650 mm Hg

Moisture Content Before Dryer: (max) 0.5% Dried Oil Moisture: (max) 0.15%

No of Noozles : 12

Nozzle Material : SUS304

Drier Chamber Material : Mild Steel (Standard) or SUS304*(by request)

Dimension Drier Chamber : (Ø) 800mm x (H) 3000mm x (T) 8mm

Float Tank Material : Mild Steel (Standard) or SUS304*(by request)

Dimension Float Tank : (H) 520mm (W) 350mm (L) 450mm

ACCESSORIES INCLUDED:

- 3 nos pipe spray nozle stainless steel 12 pcs
- 1 Pcs of Needle Valve
- 4 pcs sight glass control
- 1 unit temperature gauge 6" WIKA, Germany. Range: 0 to 160 Deg C

AVAILABLE FOR WEAR-AND-TEAR SPARE PARTS

- Nozzle stainless steel B45
- VTV Needle Valve
- VTV Sight glass
- WIKA Pressure Gauge 4" Range: 0 s/d -760 mmHg
- WIKA temperature gauge 6". Range: 0 to 160 Deg C



ADDITIONAL EQUIPMENT WE CAN SUPPLY

- Liquid Ring Vacuum Pump (European Brand)
- Dried Oil Pump (European Brand)

